



**ETRTO - WHEEL-RIM
COMPATIBILITY TABLE
“EUROPEAN TYRE
AND RIM TECHNICAL ORGANISATION”**

ETRTO COMPATIBILITY TABLE

As of 2021, this table is only valid for wheels to which the “Rim-Tyre-Pressure-Compatibility Table” is not applicable, as specified in the document, available at www.campagnolo.com.

- Before fitting the clincher tyres, check that the diameter indicated on the clincher tyre is 622 mm and that the width of the clincher tyre is compatible with the width of the rim, in accordance with the ETRTO rim/clincher tyre compatibility table (“European Tyre and rim technical organisation standard manual”).

ETRTO COMPATIBILITY TABLE “EUROPEAN TYRE AND RIM TECHNICAL ORGANISATION”																
RIM WIDTH (mm)	CLINCHER TYRE SECTION WIDTH															
	18	20	23	25	28	32	35	37	40	44	47	50	54	57	60	62
13c	✓	✓	✓	✓												
15c			✓	✓	✓	✓										
17c				✓	✓	✓	✓	✓	✓	✓	✓	✓				
19c					✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
21c							✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
23c								✓	✓	✓	✓	✓	✓	✓	✓	✓
25c										✓	✓	✓	✓	✓	✓	✓
27c											✓	✓	✓	✓	✓	✓
29c												✓	✓	✓	✓	✓

- Carefully check that the tyre beads are correctly positioned on the rim in a uniform manner along the entire circumference of the wheel.



WARNING!

Incorrect rim/ clincher tyre coupling may cause the tyre to deflate, burst or detach suddenly and cause accidents, serious injury or even death.